



FUEL OX® ASPHALTENE



Fuel Ox® Asphaltene additive is a unique, proprietary fuel treatment. It is designed to improve vehicle performance and extend engine longevity. The enhanced stability and dispersant/detergent features make it indispensable in dealing with problem fuels or fuels in storage. It removes and inhibits the formation of asphaltenes.

Fuel Ox® Asphaltene works in any combustible engine including trucks, off-road vehicles, heavy equipment, trains, and ships. Thorough testing and application has proven this additive to be compatible and 100% soluble with all types of middle distillate and heavy fuel oils.

FEATURES

- 1 ounce of Fuel Ox® Asphaltene treats up to 80 gallons of fuel
- Inhibits & removes the formations of asphaltenes
- Completely soluble in all petroleum based fuels including diesel, kerosene, and heavy fuel oils
- Cleans out fuel system & removes sludge
- Lubricates fuel system
- Increases horsepower
- Protects against corrosion
- Protects against ethanol issues
- Removes water
- Increases fuel efficiency by as much as 5-10%
- Reduces emissions by as much as 50% or more
- Stabilizes fuel for up to two years

SPECIFICATIONS

APPEARANCE:	Amber to Orange Liquid
ODOR:	Organic, Solvent
FLASH POINT:	164°F PMCC
FORM:	Liquid
SOLUBILITY IN FUEL:	100%
VISCOSITY @ 40°C:	12.9 cps
DENSITY:	6.86 lbs/gal
FLAMMABILITY:	Combustible liquid
TREATMENT RATIO:	1 : 10,000
CERTIFICATIONS:	ASTM (D-975)

STANDARDS

- American Society for Testing and Materials Specification (ASTM-D975)
- Naval Sea Systems Command (SEA 51222)
- Military Specification (MIL-L87177a)
- Department of Defense Specification (DOD-A-24682)
- Environmental Protection Agency (EPA) Registered

TREATMENT RATIO

US SIZE	METRIC SIZE	GALLONS TREATED	LITERS TREATED
16 ounces	500 ml	1,250 gallons	5,000 L
1 gallon	3,785 ml	10,000 gallons	37,854 L
55 gallon drum	208 liter drum	550,000 gallons	2,080,000 L